



Materials Supply Partners

Aqueous Cleaner P3001

Product group	Equipment Cleaning Solvent										
Characteristics	<p>Aqueous cleaner P3001 is a water soluble cleaner for the removal of water based paint from painting equipment including, spray-guns, pumps, fluid-lines, flow-cups, brushes and spray-booths etc</p> <p>It allows cleaning even after a short curing time, has no unpleasant odour and offers good value in cost per area cleaned</p>										
Instructions for use	<p>Use as supplied and without dilution at ambient temperature.</p> <p>Can be used by immersion, circulation, brushing, spraying and swabbing. Spray gun cleaning machines should be completely filled with the product and dedicated to cleaning of water based paints.</p> <p>Store between 0°C and 25°C</p>										
Technical Characteristics	<table><tr><td>Appearance –</td><td>Liquid</td></tr><tr><td>Density –</td><td>0.94 (at 20°C)</td></tr><tr><td>Flashpoint –</td><td>28°C (ISO 2592)</td></tr><tr><td>Evaporation Rate –</td><td>0.2 (NFT 30301)</td></tr><tr><td>Halogenated Hydrocarbons -</td><td>None</td></tr></table>	Appearance –	Liquid	Density –	0.94 (at 20°C)	Flashpoint –	28°C (ISO 2592)	Evaporation Rate –	0.2 (NFT 30301)	Halogenated Hydrocarbons -	None
Appearance –	Liquid										
Density –	0.94 (at 20°C)										
Flashpoint –	28°C (ISO 2592)										
Evaporation Rate –	0.2 (NFT 30301)										
Halogenated Hydrocarbons -	None										
Packing	5 lt, 20 lt and 200 lt										
Safety precautions	<p>Carry out safety risk assessment using the msds available from Pexa. Wear suitable gloves, avoid breathing or swallowing the product. Wear suitable eye protection, in case of contact with eyes or skin, rinse immediately with copious amounts of water. Provide sufficient ventilation and vapour extraction at the point of use. Use and store in a ventilated space away from flame and heat sources.</p>										
Warranty	<p>The information provided is to the best of our knowledge correct. However, we do not assume legal responsibility for use or reliance thereon. We disclaim all warranties expressed or implied including the fitness for a particular purpose. Data may be subject to modification without prior notice. Data sheets are revised every three years, please check validity.</p> <p>Issue 1 March 2006</p>										